

Standards: EN 15154-2 ANSI/ISEA Z358.1-2014 Water Flow: 11,4 lt / min for Eyewash Total Weight: 5 kgs Packed Dimensions: 32 x32 x 23 cm

Static test pressure : 7 bar Min using pressure : 1,4 bar Max using pressure : 2,8 bar

NO. DESCRIPTION

MATERIAL

OLIOTA							
1	Eyewash Bowl (Ø300mm)	Stainless Steel 304					
2	1/2" Ball Valve	Stainless Steel 304					
3	Water Outlet 1 1/4" (Female)	Stainless Steel 304					
4	Push Handle Control for Eyewash	Stainless Steel 304					
5	Water Inlet 1/2" (Female)	Stainless Steel 304					
6	Spray Nozzles	Brass					
7	Dust Cover on Eyewash Spray	Plastic					
8	Ø3 mm Water Drain for pipes	Stainless Steel 304					

										T]
		Α			FIRST ISSUE		SS	FA	ST	1	
		REV.	DATE			DESCRIPTION		DESIG	NED CHECK	ED APPROVED	1
S	FOR INFORMATION		FOR RFQ/DESIGN	×		ORIGINAL	EDITION		SIZE	SCALE	Г
STATU	FOR REVIEW					DESIGNED V	SS		A 4	1/100	1
ZS	FOR APPROVAL				~ + _	APPROVED V	FA ST		A4	17100	L

WALL MOUNTED, WITH FLANGED, STAINLESS STEEL EYE/FACE WASH PRODUCT

DRAWING NUMBER/DATE:	SHEET:	DRAWING NAME:		
3716/1	_ 1	00 1501 100		
	OF:	23-1501-100		