


Standards: EN 15154-1, EN 15154-2
 Water Flow: 11,4 lt/min for Eyewash
 75,7 lt/min for Shower
 Total Weight: 105 kg
 Packed Dimensions: 255x101x65 cm

Static test pressure : 7 bar
 Min using pressure : 1,4 bar
 Max using pressure : 2,8 bar

-side view-

-front view-



section A-A

NO.	DESCRIPTION	MATERIAL
14	Rakor(IP67)	Brass
13	Thermostat Box(IP66)	Non-exproof
12	Push Handle Control for Eyewash	Stainless Steel 304
11	1 1/4" Pipe	Stainless Steel 304
10	Pull Rod Control for Shower	Stainless Steel 304
9	Emergency Sign	PVC (Luminous)
8	Electrical Heating Tape	Ex-proof (Zone I)15 W / m
7	Spray Nozzles	Brass
6	1" Water Inlet (FNPT)	Stainless Steel 304
5	Insulation	Polietilen
4	Digital Thermostat(IP65-IP20)	Non-exproof
3	Junction Box(IP67)	Non-exproof
2	1" Ball Valve	Stainless Steel 304
1	Shower head	Polyethylene(Green)

						CUSTOMER	
REV. DATE		DESCRIPTION		DESIGNED	CHECKED	APPROVED	
A		FIRST ISSUE		SS	FA	ST	
STATUS FOR INFORMATION <input type="checkbox"/> FOR REVIEW <input type="checkbox"/> FOR APPROVAL <input type="checkbox"/>	FOR INFO/DESIGN <input checked="" type="checkbox"/>		ORIGINAL EDITION		SIZE	SCALE	PRODUCT FREEZE PROOF CABLE HEATED AND INSULATED EMERGENCY SHOWER AND EYEWASH
			DESIGNED	SS	A4	1/100	
			CHECKED	FA			
			APPROVED	ST			
				DRAWING NUMBER/DATE:		SHEET: 1	DRAWING NAME: 23-1503-450
				44/16-1		OF: 1	