


Standards: EN 15154-1, EN 15154-2
Water Flow: 11,4 lt/ min for Eyewash
75,7 lt / min for Shower
Total Weight: 105 kg
Packed Dimensions: 255x101x65 cm

Static test pressure : 7 bar
Min using pressure : 1,4 bar
Max using pressure : 2,8 bar



section A-A

NO.	DESCRIPTION	MATERIAL
13	Rakor(IP67)	Brass
12	Push Handle Control for Eyewash	Stainless Steel 304
11	1 1/4" Pipe	Stainless Steel 304
10	Pull Rod Control for Shower	Stainless Steel 304
9	Emergency Sign	PVC (Luminous)
8	Electrical Heating Tape	Ex-proof (Zone I)15 W / m
7	Spray Nozzles	Brass
6	1" Water Inlet (FNPT)	Stainless Steel 304
5	Insulation	Polietilen
4	Mechanical Thermostat(IP66)	Exproof
3	Junction Box(IP67)	Exproof
2	1" Ball Valve	Stainless Steel 304
1	Shower head	Polyethylene(Green)

							CUSTOMER						
		A		FIRST ISSUE	SS	FA				ST			
		REV.	DATE	DESCRIPTION	DESIGNED	CHECKED				APPROVED			
STATUS	FOR INFORMATION	<input type="checkbox"/>	FOR RFQ/DESIGN	<input checked="" type="checkbox"/>		ORIGINAL EDITION		SIZE	SCALE	PRODUCT	FREEZE PROOF CABLE HEATED AND INSULATED EMERGENCY SHOWER AND EYEWASH EXPROOF		
	FOR REVIEW	<input type="checkbox"/>				DESIGNED	✓					SS	
	FOR APPROVAL	<input type="checkbox"/>				CHECKED	✓					FA	
						APPROVED	✓					ST	
											DRAWING NUMBER/DATE:	SHEET: 1	DRAWING NAME: 23-1503-460
											44/16-1	OF: 1	