

# Stepp-On platform showers

## Model 24-7430

### PRODUCT INFORMATION SHEET

#### **Body- and eye-/face shower combination, frost-proof, with frame for connection below ground.**

Body- and eye shower combination, frost-proof, with frame and grating for foot operation, suitable for connection below ground.

Consists of a frost-proof valve with body shower, eye/face shower, for foot and/or hand operation, mounted in the stand-pipe of the body shower, frame with grating. Stainless steel railing around the grating.

The grating (600 x 800 mm.) is connected with a 'triangle shaped' connected cable to the push plate of the frost-proof valve. By standing on the grating, the frost-proof valve will open automatically which immediately activates the eye shower. The body shower has a separate 1" ball valve with pull rod. This way, the eye-/ face shower can be used without having to activate the body shower.

If the grating is accidentally blocked, the frost-proof valve can be used manually by pushing down the push plate. The valve will stay open until the push plate is pushed back. Eye-/ face shower (impact resistant plastic ABS), with two sprayheads that give plenty of water via an air injected spray which rinses effectively without unpleasant side effects.

Comes with two dust covers.

The 1" valve of the body shower, with full culvert, mounted in the horizontal pipe on top opens by pulling down the pull rod. The valve will stay open while using the shower.

The 1" valve is not self-closing, it closes by putting the pull rod in its original position. The showerhead of the body shower is made of impact resistant plastic ABS.

The frost-proof valve has a separate non water feeding operational pillar. It is constructed in such a way the closing of the stop valve goes gradually and slow. Because of this, water hammer in the drink water pipeline is largely prevented.

The frost-proof valve is not self-closing, the water supply can be closed with the push plate. When this happens, the water supply closes and drains the standpipe via the 5 drain holes on the bottom of the frost-proof valve. This makes the unit water free. After installing the shower, the complete headwork of the frost-proof valve can be removed easily, without too much dismantling.

# Stepp-On platform showers

## Model 24-7430

### PRODUCT INFORMATION SHEET (CONTINUED)

#### **Body- and eye-/face shower combination, frost-proof, with frame for connection below ground.**

##### ***Technical data;***

ABS eye-/face shower

ABS showerhead

1" ball valve; chrome-plated brass

Handle, extension spring, pull rod and frame; stainless steel

Railing: stainless steel

Grating, pipes and fittings; hot dip galvanised

Complete with safety sign

##### ***Frost-proof valve;***

2" outside pipe, 1" inside pipe and push plate; hot dip galvanised

Body, cover and headwork; brass

Control spindle and clamp; stainless steel

*Valve is frost-proof if water supply is provided with "heat tracing"*

##### **Water supply:**

**1 1/4" BSP female**

##### **Minimal water pressure:**

**1 bar**

##### **Capacity:**

**Body shower : approx. 80 litres/min. (2 bar)**

**Eye shower : approx. 14 litres/min. (2 bar)**

**Complies with EN 15154.**

*Technical changes reserved.*